


Mallory

LIMESTONE | TUMBLED

A very dense, clean stone with occasional markings and subtle tonal variations from ivory to pale grey. It's like a marble floor that has mellowed with age, giving large spaces an instant lived-in look that isn't overly rustic.

Suitability: Domestic/heavy commercial interior walls & floors, sealing required



CREDIT: John Evans Design, Billy Bolton Photography

Formats

Format	Availability
40 x 40 x 1.2cm	Usually in stock
40 x 60 x 1.2cm	Usually in stock

Please note: Image shows cabochons - these are additional items and will need to be ordered separately.

Technical Data

Petrographic Description

Bioclastic Calciferous Limestone.

Test	Standard	Result
Apparent Density	BS EN 1936 : 2006	2527kg/m ³
Open Porosity	BS EN 1936 : 2006	5.9%
Flexural Strength (3 Point)	BS EN 12372 : 2006	20MPa
Abrasion Resistance	BS EN 14157 : 2004	21.8mm
Slip Resistance (Dry)	BS EN 14231 : 2003	PTV 60
Slip Resistance (Wet)	BS EN 14231 : 2003	PTV 38

- ✓ Suitable for use with underfloor heating
- ✓ Suitable for use in wet areas

For any further information or advice, please contact our team.

Installation, Care & Maintenance Advice

Please refer to the installation guides on our website.