


Cherington

SANDSTONE | ETCHED/TUMBLED

A high-quality European Sandstone, warm beige in tone with occasional darker markings, similar to buff York stone.

Suitability: External paving, pool surrounds, sealing required



PAVING



COBBLES



COPING

Formats

Option	Format	Availability
Paving (Etched)	60 x 90 x 3cm	Usually in stock
Bullnose Coping (Etched)	40 x 100 x 4cm	Usually in stock
Cobbles (Tumbled)	14 x Random x 6.5cm	Usually in stock
Slab 4cm (Etched)	-	Special order

Bespoke Options



Technical Data

Test	Standard	Result
Apparent Density	BS EN 1936 : 2006	2410kg/m ³
Open Porosity	BS EN 1936 : 2006	12.6%
Compressive Strength	BS EN 1926 : 2006	73MPa
Flexural Strength (3 Point)	BS EN 12372 : 2006	8.5MPa
Frost Resistance (56 Cycles)	BS EN 12371 : 2010	7.9MPa
Abrasion Resistance	BS EN 14157 : 2004	25mm
Slip Resistance (Etched) (Dry)	BS EN 14231 : 2003	PTV 94
Slip Resistance (Etched) (Wet)	BS EN 14231 : 2003	PTV 78

- ✓ Suitable for use in wet areas
- ✓ Suitable for use in freezing temperatures

For any further information or advice, please contact our team.

Installation, Care & Maintenance Advice

Please refer to the installation guides on our website.

Product Notes

When used externally, the appearance of this stone will change over time. For more information on this, please see the info sheet 'Understanding Weathering of Natural Stone' on our website.