


Radcliffe

SLATE | RIVEN

These natural slate tiles are finely riven with calibrated thickness and subtle variations in tone for an urban look and feel.

Suitability: Domestic/light commercial interior walls & floors, sealing required



PARQUET



HEXAGON



CHEVRON



40 X 60CM TILE

Formats

Format	Format	Availability
Tile	40 x 60 x 1cm	Usually in stock
Chevron	5 x 30 x 1cm	Usually in stock
Hexagon	21.5 x 25 x 1cm	Usually in stock
Parquet	9 x 50 x 1cm	Usually in stock
2cm Slab	-	Usually in stock
3cm Slab	-	Usually in stock
Bespoke Options		

Technical Data

Petrographic Description

Fine to very fine grained, very well compacted Slate, moderately hard and robust (subjective assessment). Exhibits smooth cleavage planes and generally close slaty cleavage. The cleavage was parallel to the principal surfaces. Very few closed fractures/joints running across the cleavage planes.

Test	Standard	Result
Apparent Density	BS EN 1936 : 2006	2740kg/m ³
Open Porosity	BS EN 1936 : 2006	0.8%
Water Absorption at Atmospheric Pressure	BS EN 13755 : 2008	0.4%
Flexural Strength (3 Point)	BS EN 12372 : 2006	27.5MPa
Abrasion Resistance	BS EN 14157 : 2004	25mm
Thermal Shock Resistance	BS EN 14066 : 2013	19.9MPa
Slip Resistance (Dry)	BS EN 14231 : 2003	PTV 66
Slip Resistance (Wet)	BS EN 14231 : 2003	PTV 51

- ✓ Suitable for use with underfloor heating
- ✓ Suitable for use in wet areas

For any further information or advice, please contact our team.

Installation, Care & Maintenance Advice

Please refer to the installation guides on our website.