


Verdon

LIMESTONE | SATINO

With a soft, tactile, powdery-grey tone, a lightly antique-looking finish and subtle markings, this stone has a truly elegant, clean effect- perfect for both traditional and grand contemporary stylings.

Suitability: Domestic/Light commercial interior walls and floors, sealing required



Formats

Format

61 x Random x 1.8cm

Availability

Usually in stock

Technical Data

Petrographic Analysis

Sedimentary rock with arenaceous look, grey- beige in colour, with heterogeneous texture and fabric.

Test	Standard	Result
Water Absorption at Atmospheric Pressure	BS EN 13755 : 2008	3.3%
Flexural Strength (3 Point)	BS EN 12372 : 2006	11MPa
Abrasion Resistance	BS EN 14157 : 2004	28.5 mm
Thermal Shock Resistance	BS EN 14066 : 2013	-0.22%
Apparent Density	BS EN 1936 : 2006	2484-2499kg/m ³
Slip Resistance (Dry)	ASTM C170	PTV 78
Slip Resistance (Wet)	ASTM C170	PTV 64

- ✓ Suitable for use with underfloor heating
- ✓ Suitable for use in wet areas
- ✓ Suitable for use near heat sources

For any further information or advice, please contact our team.

Installation, Care & Maintenance Advice

Please refer to the installation guides on our website.